GUANGZHOU TESTING CENTER OF INDUSTRIAL MICROBIOLOGY TEST REPORT

Date Received: November 17, 2017
Date Analyzed: December 06, 2017

× (Date Received: November 17, 2017 Date Analyzed: December 06, 2017					
Name of Sample	TEQOYA TIP 24	Source of Sample	Delivery			
Applicant	TEQOYA SAS	Client	Liu Zheng TEQOYA 1PCS			
Manufacturer	TEQOYA	Brand				
Type and Specification		Quantity of Sample				
Date of Production	7°	Sample description	Machine (Black)			
Batch Number		Packing of Sample	In box			
Sample Picture						
Standard and Methods	<technical disinfec<="" for="" standard="" td=""><td>tion>2002-2.1.3 Air disinfection of</td><td>effect evaluation test</td></technical>	tion>2002-2.1.3 Air disinfection of	effect evaluation test			
Items of Analysis	Air Disinfection Examination (Natural bacteria in air)					
Remarks			5			

To be continued

GUANGZHOU TESTING CENTER OF INDUSTRIAL MICROBIOLOGY TEST REPORT

Date Received: November 17, 2017 Date Analyzed: December 06, 2017

Method for testing air disinfection (Natural Bacteria):

- 1. Test equipments:
 - 1) Culture media: NA
 - 2) Sampling equipment: six-stage sieve sampler
- 2. Test conditions:
 - 1) The volume of the test chamber: 10 m³
 - 2) Environment temperature: (20~25) °C
 - 3) Environment humidity: (50~60)% RH
- 3. Operation conditions of the machine
 - Set the switch to position "Electricity to boot".
- 4. Test Procedure
 - 1) The equipments are placed in the test chamber, close the door, and collect natural bacteria by six-stage sieve sampler, as the original bacteria count (positive control).
 - 2) The air cleaner is adjusted to the highest air cleaning mode setting for test, operating the unit for 120 min. The natural bacteria are collected by six-stage sieve sampler, as the bacteria count after treatment.
 - 3) In sampling, place the sampling equipment in the center of test chamber at the height 1.0 meters.
 - 4) Choose 2 NA plates (the same batch) as the negative control, and culture them on the same condition as the samples.
 - 5) The tests repeat three times, and calculate the killing rate respectively.
- 2. Killing Rate $K_t(\%) = \frac{V_0 V_t}{V_0} \times 100$

Where: V_0 = Original Bacteria Count; V_t = Bacteria Count after Treatment.

Test results

rest results					Li la	
Number of Sample	Test Bacteria	Test time (min)	Test Number	Original Bacteria Count V_0 (cfu/m 3)	Bacteria Count after Treatment V_t (cfu/m 3)	Killing Rate <i>K</i> , (%)
0		0,	1	2.75×10 ⁴	1.52×10 ³	94.47
KJ20171795-1	Natural bacteria in air	120	A2**	3.51×10 ⁴	2.23×10 ³	93.65
			3	2.41×10 ⁴	1.14×10³	95.27

报告结束/End of report

Page 2 of 2

Editor 7 # 4

Checker Alssuer

本今

Date Reported

